

ABOUT ROBYTOWER

ROBYTOWER is a motorized telescopic column specifically designed for professional broadcasting needs. Either for studio application or a an outdoor event, RobyTower is a perfect solution to achieve smooth panoramic shots. The system can be used upright achieving a variety of shots from 1,4 m to 4,4 m high or be installed in a hanging position (optional).

The system is built of strong, narrow aluminum tubes, which make the whole construction extremely compact and light-weight. All parts are assembled to guarantee maximum stability and rigidness in challenging broadcast environments. The system works perfectly with gyro-stabilized heads Robyhead L and Robyhead R3, but is also compatible with a standard PTZ head like Robyhead D1.


The system is controlled through a regular control panel or a floor pedal for height control. RobyTower is very easy and quick to mount. Normally a flat plate is used as a base, however the system can also be mounted on a wheeled dolly.

RECENT REFERENCE

2021 Russian Premier League matches

ROBYTOWER SYSTEM FEATURES

Maximum speed 1,5 m/s	Acceleration 1 m/s²
Weight 60 kg	Payload 20 kg
Maximum height 4,5 m	Compatible heads: Gyro-stabilized Roby- head L, R3, PTZ Roby- head D1
Voltage 220 V, 1,5 KW	
	⊙ Universal flate plate as a basement
⊗ Borders preset	O Upright/hanging positioning (optional)



Head placement size:

Min 1487 mm Max 4337 mm

